


## Features:

- On-board Ultra low noise 3.3 V voltage regulator and RF filter for noise blocking
- **USB** and **UART (Tx,Rx)** interfaces **RAW data** out avail
- **LIS3MDL** I2C magnetometer
- **Double band Pass filter** for noise rejection
- **Double LNA with very low noise figure**
- **Triple band** GPS, Glonass, Beidou antenna
- Mini USB connector
- Time pulse LED
- u-center GPS evaluation software
- Extensive visualization and evaluation features
- EMI and RFI protection
- Backup supercapacitor
- Dimensions: Round 100 mm hole distance 45x45 mm
- Weight 51 gram

## Reference: ELT0046



### GNSS FEATURES

Receiver type	72-channel u-blox M8 engine GPS/QZSS L1 C/A, GLONASS L10F, Beidou B1I, Galileo E1B/C, SBAS L1 C/A: WAAS, EGNOS, MSAS, GAGAN
GNSS platform	Concurrent GNSS
GNSS bands	L1C/A, L10F, E1-B/C, B1I
Oscillators	TCXO

### PERFORMANCE

Position accuracy	2.0 m CEP (with SBAS) 2.5 m CEP (without SBAS)
Acquisition	Cold start Hot start Aided start Nav.update rate
GPS+GLONASS	26 s 1 s 2 s 5 Hz
GPS	29 s 1 s 2 s 10 Hz
GLONASS	30 s 1 s 2 s 10 Hz
Beidou	34 s 1 s 3 s 10 Hz
Galileo	45 s 1 s 7 s 10 Hz
Velocity accuracy	0.05 m/s
Dynamic heading accuracy	0.3 deg
Sensitivity (GPS+GLO):	
Tracking and Navigation	-167 dBm
Reacquisition	-160 dBm
Cold start	-148 dBm
Hot start	-157 dBm

### OTHER FEATURES

Anti-jamming	Additional SAW filter and LNA
Anti-spoofing	Spoofing detection
Memory	Flash
Operating temperature	0 °C to +50 °C
Supply voltage	4.5 V to 5.5 V
Supply current	<45 mA